THE C CANDLEMAKERS SAFETY DATA SHEET S STORE

Section 1. Identification

Product name	: VYBAR™ 103 POLYMER
	™ a trademark of Baker Hughes, Inc.
Product code	: 20272015
Relevant identified uses of the	e substance or mixture and uses advised against
Identified uses	: Numerous uses.
Print date	: 2/17/2019
Validation date	: 2/17/2019
Version	: 1
Supplier's details	: The Candlemaker's Store
	4951 Hamilton-Middletown Road
	Liberty Township, OH 45011
	For Product Information/MSDSs Call:513-868-9425
	(9:00 a.m3:00 p.m. est, Monday - Friday) E-mail inquiries to: candlemakers@fuse.net
Emergency telephone	CHEMTREC: 800-424-9300 (U.S. 24 hour)
number (with hours of	-0.00000000000000000000000000000000000
operation)	

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	: COMBUSTIBLE DUSTS
substance or mixture	
GHS label elements	
Signal word	: Warning
Hazard statements	: May form combustible dust concentrations in air.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	 Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Prevent dust accumulation.
Hazards not otherwise classified	 Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture

: Substance

Ingredient name	%	CAS number
Alkenes, α-, polymerized	90 - 100	Trade secret*

Additional information

* The CAS number for use in the United States is Baker Hughes confidential business information. For use outside the United States, the CAS Number for this component is 68527-08-2.

Section 4. First aid measures

Description of necessary fir	st aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important sym	otoms/effects, acute and delayed
Potential acute hea	Ith effects
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure sigr</u>	<u>is/symptoms</u>
Eye contact	: irritation, redness
Inhalation	: respiratory tract irritation, coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate med	ica	l attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 4. First aid measures

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fig	hting measures
Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Fine dust clouds may form explosive mixtures with air.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Remark	: As with most solid particulate organic materials, high concentrations of dusts from this product suspended in air are an explosion hazard in the presence of sparks, flames, and heat. Do not allow dust to accumulate on equipment and surfaces where this product is used. In the National Fire Protection Association (NFPA) Code 499, a "combustible dust" is any finely divided solid material 420 microns or less in diameter that presents a fire or explosion hazard when dispersed in air. This product would be a Group G combustible dust, but there is no Layer or Cloud Ignition Temperature available for it. When there is the potential of a dust explosion in a use location, the proper electrical equipment and installation should be used.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Dike spill area and do not allow product to reach sewage system or surface or ground water. Notify any reportable spill to authorities. (See section 12 for environmental risks and 13 for disposal information.) Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. To clean the floor and all objects contaminated by this material, use detergent solution. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Additional information	

Packaged material (boxes, bags) should be stored in conditions that avoid extremes of temperature. When temperature extremes are avoided, this product has an expiration date of three years from the date of manufacture. The expiration date can be extended for an additional three year interval if the batch is recertified by the manufacturer. When the product is melted for use, care must be taken to avoid overheating the molten wax and causing oxidation of the product.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits			TWA (8 hours)			STEL (15 mins)			g		
Ingredients:	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
	US ACGIH US ACGIH OSHA PEL OSHA PEL		10 3 5 15	-	- - -	- - -	- - -			-	[a] [b] [c] [d]

Section 8. Exposure controls/personal protection

Form: [a]Inhalable fraction. [b]Respirable fraction [c]Respirable dust [d]Total dust

Consult local authorities for acceptable exposure limits.

Only components of this product with established exposure limits appear in the box above. If OSHA permissible exposure levels are shown above they are the OSHA 1989 levels or are from subsequent OSHA regulatory actions. Although the 1989 levels have been vacated the 11th Circuit Court of Appeals, the manufacturer recommends that these lower exposure levels be observed as reasonable worker protection.

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	 Wear chemical safety goggles. When transferring material wear face-shield in addition to chemical safety goggles.
Hand protection	: Chemical-resistant gloves.
Skin protection	: Wear long sleeves to prevent repeated or prolonged skin contact.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Appearance	
Physical state	: Solid. [Pastilles.]
Color	: Off-white.
Odor	: Little or none.
Odor threshold	: Not available.
рН	: Not available.
Melting/freezing point	: 65.6 to 82.2°C (150.1 to 180°F)
Boiling point	: Not available.
Initial Boiling Point	: Not available.
Flash point	: Open cup: >175°C (>347°F) [Cleveland.]
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: As with most solid particulate organic materials, high concentrations of dusts from this product suspended in air are an explosion hazard in the presence of sparks, flames, and heat. Do not allow dust to accumulate on equipment and surfaces where this product is used. In the National Fire Protection Association (NFPA) Code 499, a "combustible dust" is any finely divided solid material 420 microns or less in diameter that presents a fire or explosion hazard when dispersed in air. This product would be a Group G combustible dust, but there is no Layer or Cloud Ignition Temperature available for it. When there is the potential of a dust explosion in a use location, the

proper electrical equipment and installation should be used.

Section 9. Physical and chemical properties

Lower and upper explosive (flammable) limits	1	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	0.91 to 0.93 (15.6°C)
Density	:	7.58 to 7.75 (lbs/gal)
Solubility in water	:	Insoluble
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
Viscosity	;	Dynamic (99°C): 200 to 500 cP
VOC	:	0 g/l
Pour Point	:	Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
VYBAR™ 103 POLYMER	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

No applicable toxicity data

Sensitization

No applicable toxicity data

Mutagenicity

No applicable toxicity data

Carcinogenicity

Section 11. Toxicological information

No applicable toxicity data	
Reproductive toxicity	
No applicable toxicity data	
Teratogenicity	
No applicable toxicity data	
Specific target organ toxicit	t <u>y (single exposure)</u>
Not applicable.	
Specific target organ toxicit	t <u>y (repeated exposure)</u>
Not applicable.	
Aspiration hazard	
Not available.	
Information on the likely routes of exposure	: Routes of entry anticipated: Dermal, Inhalation.
	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	e <u>cts</u>
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Additional information

The Primary Dermal Irritation Index for this product is 0.0 out of 8. Thus the product is considered non- irritating to the skin by rabbit skin tesing.

Section 12. Ecological information

Toxicity

No applicable toxicity data

Persistence and degradability

Not available.

Section 12. Ecological information

Other adverse effects **Additional information**

: No known significant effects or critical hazards.

This product would be expected to biodegrade slowly, depending upon the conditions to which it is exposed. Under OECD Method 310D, the biodegradability is less than 25% after five days.

Ecotoxicological data on analogous polymeric materials demonstrates that the polymers in this product have a low aquatic toxicity to fish, algae, and daphnia. Under OECD guidelines this product is classed as inherently biodegradable. The product is unlikely to bioaccumulate due to the large polymeric nature of the polymers. Classification according to German Umweltbundesamt.de is "nwg".

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	Remarks If transported in bulk above 100 C (212 F), product must be shipped as "Elevated temperature liquid, n.o. s., 9, UN3257, III"	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport information

Transport in bulk according : Not available		
to Annex II of MARPOL		
73/78 and the IBC Code		
DOT Reportable Quantity	Not applicable.	
Marine pollutant	Not available.	

North-America NAERG

: Not available.

Section 15. Regulatory information		
: TSCA 12(b) one-time export: No products were found.		
TSCA 12(b) annual export notification: No products were found.		
United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: No products were found.		
Clean Water Act (CWA) 311: No products were found.		
: Not listed		
: No products were found.		
: Fire hazard		
: No products were found.		
: All components are listed or exempted.		
 Australia inventory (AICS): All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. Japan inventory: All components are listed or exempted. Korea inventory: All components are listed or exempted. Malaysia Inventory (EHS Register): Not determined. New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted. 		

Additional information

This product meets the requirements of the following U.S.A. food additive regulations: 21 CFR §§ 175.105¹, 176.170¹, 176. 180¹, and 178.3850¹. (¹extraction limitations and other possible restrictions)

Section 16. Other information

National Fire Protection Association (U.S.A.)



History Date of printing

: 2/17/2019

Section 16. Other information

Indicates information that has changed from previously issued version.

Notice to reader

NOTE: The information on this MSDS is based on data which is considered to be accurate. The manufacturer, however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This MSDS was prepared and is to be used for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Because it has become common for purchasers of our products to file patents for specific end uses of our products, Baker Hughes and The Candlemaker's Store advises its customers to research their particular end use for possible intellectual property issues with respect to third party patents.