# SAFETY DATA SHEET



### 1. Identification

Product identifier 4700 - 4800 Series Products (Astorlite®, Nochek®, Parafflex®, Synertive®)

Other means of identification

**SDS number** 4700 - 4800 Series (929125)\_USA\_English

Synonyms See page 8

Recommended use Further processing, Misc. multiple uses

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name The International Group Inc.

Address 50 Salome Dr.

Toronto

ON, M1S2A8, CA
Telephone +1 416-293-4151
Emergency phone number +1 416-293-4151

+1 800-561-3509

**CHEMTREC (North** 

America)

+1 800-424-9300

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

**Precautionary statement** 

**Prevention** Observe good industrial hygiene practices.

Response Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Paraffinic Hydrocarbons	Proprietary	≤ 90
Fatty acid	Proprietary	< 17

Composition comments The specific chemical identity and/or exact percentage of component(s) have been withheld as a

trade secret.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

**Inhalation** Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to

fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

4700 - 4800 Series SDS US

929125 Version #: 02 Revision date: 11-April-2018 Issue date: 18-August-2015 1 / 8

Skin contact Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten

material adhering to skin as quickly as possible with water, and see a physician for removal of

adhering material and treatment of burn.

Eye contact Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated

product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get

medical attention if irritation develops and persists.

Ingestion Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested,

do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention

immediately.

Most important symptoms/effects, acute and delayed Eye and skin contact: When heated, contact with molten product can cause injury and burns.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

**General information** If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

General fire hazards No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water.

Issue date: 18-August-2015

2/8

Small Spills: Where possible allow molten material to solidify naturally.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

4700 - 4800 Series SDS US

Revision date: 11-April-2018

929125 Version #: 02

## 7. Handling and storage

Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

## 8. Exposure controls/personal protection

## Occupational exposure limits

## US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Fatty acid	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Paraffinic Hydrocarbons	TWA	2 mg/m3	Fume.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Paraffinic Hydrocarbons	TWA	2 mg/m3	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency

shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory

gear is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

3/8

work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Solid. Physical state

**Form** Slabs, prills, pastilles or granules.

Color White to dark amber.

Odor None to strong petroleum odor.

No data available. Odor threshold Not applicable. рΗ

4700 - 4800 Series SDS US

929125 Version #: 02 Revision date: 11-April-2018 Issue date: 18-August-2015 Melting point/freezing point 114.8 - 257 °F (46 - 125 °C)

Initial boiling point and boiling

range

> 572 °F (> 300 °C)

> 392.0 °F (> 200.0 °C) ASTM D-92 Flash point

**Evaporation rate** < 0.01 (Butyl acetate = 1)

Flammability (solid, gas) Will support a flame above flash point.

Upper/lower flammability or explosive limits

0.9 % v/v Explosive limit - lower (%) Explosive limit - upper (%) 7 % v/v

Vapor pressure < 0.01 mm Hg 77 °F (25 °C) Vapor pressure temp. Vapor density > 5 (Air = 1)

0.9 - 0.96 (H2O=1) Relative density Relative density temperature 77 °F (25 °C)

Solubility(ies)

< 0.1 % Solubility (water) 68 °F (20 °C) Solubility temp. (water) Partition coefficient No data available.

(n-octanol/water)

No data available. **Auto-ignition temperature Decomposition temperature** No data available. **Viscosity** No data available.

Other information

< 0.01 Partition coefficient

(oil/water)

< 1 Percent volatile

#### 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

Decomposition of this product can generate carbon dioxide, carbon monoxide and other products

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

such as aldehyldes and ketones depending on conditions of oxidation.

### 11. Toxicological information

Information on likely routes of exposure

Inhalation Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax

fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

Skin contact Health injuries are not known or expected under normal use. Molten material will produce thermal

Health injuries are not known or expected under normal use. Molten material will produce thermal Eye contact

Health injuries are not known or expected under normal use. Contact with hot material can cause Ingestion

thermal burns which may result in permanent damage.

Symptoms related to the physical, chemical and toxicological characteristics Eye and skin contact: Contact with molten material may cause thermal burns.

#### Information on toxicological effects

Not expected to be acutely toxic. Acute toxicity

4700 - 4800 Series SDS US 929125 Version #: 02 Revision date: 11-April-2018 Issue date: 18-August-2015 4/8 Components Species Test Results

Fatty acid (CAS Proprietary)

<u>Acute</u> Dermal

LD50 Rabbit > 2000 mg/kg, 24 hours

Skin corrosion/irritation Not classified. Thermal burn hazard - contact with hot material may cause thermal burns.

Serious eye damage/eye

irritation

Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity Not classified.

Carcinogenicity Not expected to be hazardous by OSHA criteria.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity Not classified.

Specific target organ toxicity - Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Solid product: Not likely, due to the form of the product.

Chronic effects Exposure to vapors, fumes, or smoke from molten material handled in confined areas can

produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals.

Further information None.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available on bioaccumulation. The product is insoluble in water.

Mobility in soil The product is insolub

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

4700 - 4800 Series SDS US
929125 Version #: 02 Revision date: 11-April-2018 Issue date: 18-August-2015 5 / 8

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a

class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III

(Polyolefinic blend).

Not applicable.

# 15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

## **US. Massachusetts RTK - Substance List**

Paraffinic Hydrocarbons (CAS Proprietary)

#### US. New Jersey Worker and Community Right-to-Know Act

Paraffinic Hydrocarbons (CAS Proprietary)

## US. Pennsylvania Worker and Community Right-to-Know Law

Paraffinic Hydrocarbons (CAS Proprietary)

## US. Rhode Island RTK

Paraffinic Hydrocarbons (CAS Proprietary)

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

4700 - 4800 Series SDS US

Revision date: 11-April-2018

929125 Version #: 02

Issue date: 18-August-2015

Country(s) or region Inventory name On inventory (yes/no)\*

European Inventory of Existing Commercial Chemical Europe

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes

New Zealand **New Zealand Inventory** Yes

**Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

# 16. Other information, including date of preparation or last revision

Issue date 18-August-2015 **Revision date** 11-April-2018

Version # 02

**HMIS®** ratings Health: 0

Flammability: 1 Physical hazard: 0

**NFPA** ratings



#### Disclaimer

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

4700 - 4800 Series SDS US 7/8

929125 Version #: 02 Revision date: 11-April-2018 Issue date: 18-August-2015

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## PRODUCT NUMBER

4840A

4850B

4850C

4850E

4856A

4856C

4856E

4856F

4856G

4856H

4856M

4856N

4856P

4856Q

4856R

4856S

4856T

4857A

4857B

4857C

4857D

4857E

4857G

4857H

4857L

929125

Version #: 02

4857V

4700 - 4800 Series SDS US

Revision date: 11-April-2018

8/8

Issue date: 18-August-2015