# **Technical Data Sheet**

# NatureWax® C-1

## **PRODUCT DESCRIPTION**

A blend of hydrogenated vegetable glycerides

#### **APPLICATION**

Vegetable glycerides substitute for paraffin in wax applications

### PRODUCT NUMBERS COVERED

100085499 - NatureWax® C-1 Bulk

100085812 - NatureWax® C-1 Bulk W/TBHQ

100087409 - NatureWax® C-1 Flake

100087410 - NatureWax® C-1 Flake HT (Heat Treated Pallets)

110021724 - NatureWax® C-1 Pastilles

110021632 - NatureWax® C-1 Slab

### **TECHNICAL CHEMICAL / PHYSICAL PROPERTIES**

Chemical & Physical Analysis	Minimum	Typical	Maximum	UOM	Method
Color Red			1.5		AOCS Cc 13j-97
Free Fatty Acids as Oleic (282)			0.05	%	AOCS Ca 5a-40
Peroxide Value			1.00	meq/kg	AOCS Cd 8b-90
Iodine Value	47		55	cg/g	AOCS Cd 1-25
Mettler Dropping Point	124	126	130	°F	AOCS Cc 18-80

#### **POSSIBLE USES**

Candles: container candle wax, softener for pillar candles

Other: paper cup coatings, stationery pencils, color pencils, ink ribbons, mold lubricant, textile finishes, sizing, cord lubricant, metal lubricant, adhesives, thermoplastics resin additive, leather dressing, crayons

## **BIO-ENGINEERED STATUS**

The product(s) listed above are produced from non-identity preserved soybeans. Although genetically-engineered soybeans are used to produce our products, qualitative PCR test results for our NatureWax products have been ND (non-detectible). Further information is available upon request.



# NatureWax® C-1

### **PACKAGING & CODING**

#### **Lot Code Format**

The Lot Code is a unique number generated by our sales order system. From this unique number, we are able to trace back through our processing steps within our Quality Control System to the source oil(s).

# **SHELF LIFE, SHIPPING & STORAGE INFORMATION**

#### **Product Shelf Life**

#### **Bulk Product**

Typical bulk storage period or "shelf-life" of oils and shortenings held in bulk is three to four weeks under controlled conditions — protected from light and moisture, at the correct temperature and under nitrogen blanket.

# **Packaged Product**

18 months from Date of Pack. Testing toward end of anticipated shelf-life may suggest that shelf-life may be extended. Please request assistance if this is required.

# Shipping & Storage Conditions

#### **Bulk Product**

Bulk oils should be stored and shipped under controlled conditions to protect from light and moisture, maintain correct temperature and with nitrogen blanket. Storage conditions should be maintained so to minimize the impact of the following four (4) causes of degradation:

- 1. Heat The oil should ideally be held between 60-100°F for oils that are liquid at room temperature and 15-25°F above the melting point for oils that are solid at room temperature.
- 2. Exposure to oxygen Oxidative deterioration is the main cause for stability problems. Ways to minimize exposure to oxygen are:
  - Be sure oil does not free-fall into tank, i.e., fill from the bottom or have a downspout from the top to below the surface.
  - If a recirculation system is used, be sure there are no air leaks around flanges, pump seals, etc.
  - Only recirculate the oil long enough to maintain a homogeneous mixture, i.e., the more it is mixed, the greater the chance of deterioration.
  - If the oil is to be held for extended periods of time (over three weeks), nitrogen blanketing the tank is recommended.
- Light Light can cause deterioration of liquid wax and measures should be taken to minimize this
  exposure. This is only a problem in fiberglass tanks that are exposed to direct sunlight or indoor
  lighting steel or insulated tanks do not usually have light exposure problems.
- 4. Trace metals Trace metals such as copper and iron are extremely pro-oxidant and care should be taken to avoid any places where these substances might be introduced to the oil. Things to avoid are any fittings or valves that are constructed of copper or brass.

#### **Packaged Product**

For ease when using, store at 65-85°F. Protect from extreme heat and cold (temperatures over 90°F and under 40°F).

# Technical Data Sheet

#### CONTACT

Cargill Bioindustrial 13400 15th Ave N, Suite B Plymouth, MN 55441 1-800-842-3631 CIS customerservice@cargill.com



