USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

## PARAFFLEX® 4625A

**PARAFFLEX**® **4625A** is a specialty formulation of petroleum waxes suitable for the manufacture of scented pillar, votive and other molded candles.

## PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	135 (57.2)	147 (63.9)	142 (61.1)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	3.9	5.9	4.9
Oil Content, Wt%	D 721			0.4
Saybolt Color	D 6045	+25		+28
Odor	D 1833		2	1
Needle Penetration, dmm @ 77°F (25°C)	D 1321	10	20	18

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

## **FDA STATUS:**

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in contact with food. For additional FDA compliance information, please contact your IGI Sales Representative.

4/11/17

## WARRANTY DISCLAIMER STATEMENT